

Advance Engineering Group

SIEMENS STOCK SHEET

Brand	Series	Item Code	Stock Quantity	Description
SIEMENS	S7-1200	6ES7211-1AE40-0XB0	3	SIMATIC S7-1200, CPU 1211C, compact CPU, DC/DC/DC, onboard I/O: 6 DI 24 V DC; 4 DO 24 V DC; 2 AI 0-10 V DC, power supply: DC 20.4-28.8 V DC, program/data memory 75 KB
SIEMENS	S7-1200	6ES7211-1BE40-0XB0	3	SIMATIC S7-1200, CPU 1211C, compact CPU, AC/DC/relay, onboard I/O: 6 DI 24 V DC; 4 DO relay 2 A; 2 AI 0-10 V DC, power supply: AC 85-264 V AC at 47-63 Hz, program/data memory 75 KB
SIEMENS	S7-1200	6ES7211-1HE40-0XB0	3	SIMATIC S7-1200, CPU 1211C, compact CPU, DC/DC/relay, onboard I/O: 6 DI 24 V DC; 4 DO relay 2 A; 2 AI 0-10 V DC, Power supply: DC 20.4-28.8V DC, Program/data memory 50 KB
SIEMENS	S7-1200	6ES7214-1AG40-0XB0	17	SIMATIC S7-1200, CPU 1214C, compact CPU, DC/DC/DC, onboard I/O: 14 DI 24 V DC; 10 DO 24 V DC; 2 AI 0-10 V DC, Power supply: DC 20.4-28.8V DC, Program/data memory 100 KB
SIEMENS	S7-1200	6ES7214-1BG40-0XB0	16	SIMATIC S7-1200, CPU 1214C, compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 100 KB
SIEMENS	S7-1200	6ES7214-1HG40-0XB0	18	SIMATIC S7-1200, CPU 1214C, compact CPU, DC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, power supply: DC 20.4-28.8 V DC, program/data memory 150 KB
SIEMENS	S7-1200	6ES7215-1AG40-0XB0	2	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/DC, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO 24 V DC; 0.5A; 2 AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB
SIEMENS	S7-1200	6ES7215-1BG40-0XB0	1	SIMATIC S7-1200, CPU 1215C, compact CPU, AC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A, 2 AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 125 KB
SIEMENS	S7-1200	6ES7215-1HG40-0XB0	4	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A, 2 AI 0-10 V DC, 2 AO 0-20 mA DC, power supply: DC 20.4-28.8 V DC, program/data memory 200 KB
SIEMENS	S7-1200	6ES7221-1BF32-0XB0	22	SIMATIC S7-1200, Digital input SM 1221, 8 DI, 24 V DC, Sink/Source
SIEMENS	S7-1200	6ES7221-1BH32-0XB0	5	SIMATIC S7-1200, Digital input SM 1221, 16 DI, 24 V DC, Sink/Source
SIEMENS	S7-1200	6ES7222-1BF32-0XB0	33	SIMATIC S7-1200, Digital output SM 1222, 8 DO, 24 V DC, transistor 0.5 A
SIEMENS	S7-1200	6ES7222-1BH32-0XB0	60	SIMATIC S7-1200, Digital output SM 1222, 16 DO, 24 V DC, transistor 0.5 A
SIEMENS	S7-1200	6ES7222-1HF32-0XB0	31	SIMATIC S7-1200, Digital output SM 1222, 8 DO, relay 2 A
SIEMENS	S7-1200	6ES7222-1HH32-0XB0	26	SIMATIC S7-1200, Digital output SM 1222, 16 DO, relay 2 A
SIEMENS	S7-1200	6ES7223-1BH32-0XB0	40	SIMATIC S7-1200, Digital I/O SM 1223, 8 DI/8 DO, 8 DI 24 V DC, Sink/Source, 8 DO, transistor 0.5 A
SIEMENS	S7-1200	6ES7223-1BL32-0XB0	20	SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, transistor 0.5 A
SIEMENS	S7-1200	6ES7223-1PH32-0XB0	17	SIMATIC S7-1200, Digital I/O SM 1223, 8 DI/8 DO, 8 DI 24 V DC, Sink/Source, 8 DO, relay 2 A
SIEMENS	S7-1200	6ES7223-1PL32-0XB0	1	SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, relay 2 A
SIEMENS	S7-1200	6ES7223-1QH32-0XB0	2	SIMATIC S7-1200, Digital I/O SM 1223, 8 DI AC/8 DO RLY, 8 DI 120/230 V AC, 8 DO relay 2 A
SIEMENS	S7-1200	6ES7231-4HA30-0XB0	4	SIMATIC S7-1200, Analog input, SB 1231, 1 AI, +/-10 V DC (12 bit resol.) or 0-20 mA
SIEMENS	S7-1200	6ES7231-4HF32-0XB0	9	SIMATIC S7-1200, Analog input, SM 1231, 8 AI, +/-10 V, +/-5 V, +/-2.5 V, or 0-20 mA/4-20 mA, 12 bit+sign or (13 bit ADC)
SIEMENS	S7-1200	6ES7231-5ND32-0XB0	1	SIMATIC S7-1200, Analog input, SM 1231, 4 AI, +/-10 V, +/-5 V, +/-2.5 V, +/-1.25 or 0-20 mA/4-20 mA, 15 bit+sign bit
SIEMENS	S7-1200	6ES7231-5PD32-0XB0	1	SIMATIC S7-1200, Analog input, SM 1231 RTD, 4xAI RTD module
SIEMENS	S7-1200	6ES7231-5PF32-0XB0	10	SIMATIC S7-1200, Analog input, SM 1231 RTD, 8xAI RTD module

SIEMENS	S7-1200	6ES7231-5QF32-0XB0	5	SIMATIC S7-1200, Analog input, SM 1231 TC, 8 AI thermocouples
SIEMENS	S7-1200	6ES7231-5QD32-0XB0	5	SIMATIC S7-1200, Analog input, SM 1231 TC, 4 AI thermocouples
SIEMENS	S7-1200	6ES7232-4HA30-0XB0	13	SIMATIC S7-1200, Analog output, SB 1232, 1 AO, +/-10 V DC (12 bit resol.) or 0-20mA (11 bit resol.)
SIEMENS	S7-1200	6ES7232-4HB32-0XB0	20	SIMATIC S7-1200, Analog output, SM 1232, 2 AO, +/-10 V, 14-bit resolution, or 0-20 mA/4-20 mA, 13-bit resolution
SIEMENS	S7-1200	6ES7234-4HE32-0XB0	23	SIMATIC S7-1200, analog I/O SM 1234, 4 AI/2 AO, +/-10 V, 14-bit resolution or 0 (4)-20mA, 13-bit resolution
SIEMENS	S7-1200	6ES7241-1AH32-0XB0	17	SIMATIC S7-1200, Communication module CM 1241, RS232, 9-pole D-sub (pin), supports Freeport
SIEMENS	S7-1200	6ES7241-1CH32-0XB0	11	SIMATIC S7-1200, Communication module CM 1241, RS422/485, 9-pole D-sub (socket) supports Freeport
SIEMENS	S7-1200	6ES7241-1CH30-1XB0	12	SIMATIC S7-1200, Communication Board CB 1241, RS485, terminal block, supports Freeport
SIEMENS	Power Supply for S7-1500	6ES7505-0KA00-0AB0	3	SIMATIC S7-1500, System power supply PS 25W 24 V DC, supplies the backplane bus of the S7-1500 with operating voltage
SIEMENS	Power Supply for S7-1500	6ES7505-0RA00-0AB0	3	SIMATIC S7-1500, System power supply PS 60W 24/48/60 V DC, supplies the backplane bus of the S7-1500 with operating voltage
SIEMENS	Power Supply for S7-1500	6ES7507-0RA00-0AB0	3	SIMATIC S7-1500, system power supply PS 60W 120/230V AC/DC, supplies the backplane bus of S7-1500 with operating voltage
SIEMENS	Rail Mounting for S71500	6ES7590-1AB60-0AA0	3	SIMATIC S7-1500, mounting rail 160 mm (approx. 6.3 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays
SIEMENS	Rail Mounting for S71500	6ES7590-1AC40-0AA0	10	SIMATIC S7-1500, mounting rail 245 mm (approx. 9.6 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays
SIEMENS	Rail Mounting for S71500	6ES7590-1AE80-0AA0	10	SIMATIC S7-1500, mounting rail 482.6 mm (approx. 19 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays
SIEMENS	Rail Mounting for S71500	6ES7590-1AF30-0AA0	16	SIMATIC S7-1500, mounting rail 530 mm (approx. 20.9 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays
SIEMENS	Rail Mounting for S71500	6ES7590-1AJ30-0AA0	10	SIMATIC S7-1500, mounting rail 830 mm (approx. 32.7 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays
SIEMENS	Connector for S71500	6ES7592-1BM00-0XA0	9	SIMATIC S7-1500, Front connector in push-in design, 40-pole for 25 mm wide modules and compact CPUs of the S7-1500, incl. cable tie
SIEMENS	Connector for S71500	6ES7592-1AM00-0XB0	38	SIMATIC S7-1500, Front connector Screw-type connection system, 40-pole for 35 mm wide modules incl. 4 potential bridges, and cable ties
SIEMENS	Connector for S71500	6ES7592-1BM00-0XB0	40	SIMATIC S7-1500, Front connector in push-in design, 40-pole, for 35 mm wide modules incl. 4 potential bridges and cable ties
SIEMENS	Power Supply for S7-300	6ES7307-1EA80-0AA0	1	SIMATIC S7-300 Outdoor Regulated power supply PS307 input: 120/230 V AC, output: 24 V/5 A DC
SIEMENS	MMC S7-300	6ES7951-0KJ00-0AA0	1	SIMATIC S7, memory cards for S7-300, Short design, 5V Flash EPROM, 512 KB
SIEMENS	MMC S7-300	6ES7953-8LG31-0AA0	14	SIMATIC S7, Micro Memory Card for S7-300/C7/ET 200, 3, 3V Nflash, 128 KB

SIEMENS	MMC S7-300	6ES7953-8LJ31-0AA0	10	SIMATIC S7, Micro Memory Card for S7-300/C7/ET 200, 3, 3V Nflash, 512 KB
SIEMENS	MMC S7-300	6ES7953-8LM32-0AA0	2	SIMATIC S7, Micro Memory Card for S7-300/C7/ET 200, 3, 3V Nflash, 4 MB
SIEMENS	Front Connector S7-300	6ES7392-1AJ00-0AA0	3	SIMATIC S7-300, Front connector for signal modules with screw contacts, 20-pole
SIEMENS	Front Connector S7-300	6ES7392-1BM01-0AA0	1	SIMATIC S7-300, Front connector for signal modules with spring-loaded contacts, 40-pole
SIEMENS	ET 200SP	6ES7131-6BH01-0BA0	9	SIMATIC ET 200SP, Digital input module, DI 16x 24V DC Standard, type 3 (IEC 61131), sink input, (PNP, P-reading), Packing unit: 1 Piece, fits to BU-type A0, Colour Code CC00, input delay time 0,05..20ms, diagnostics wire break, diagnostics supply voltage
SIEMENS	ET 200SP	6ES7132-6BD20-0BA0	18	SIMATIC ET 200SP, digital output module, DQ 4x 24VDC/2A Standard, suitable for BU type A0, Color code CC02, Module diagnostics
SIEMENS	ET 200SP	6ES7132-6BF01-0BA0	19	SIMATIC ET 200SP, Digital output module, DQ 8x 24V DC/0,5A Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to BU-type A0, Colour Code CC02, substitute value output, module diagnostics for: short-circuit to L+ and ground, wire break, supply voltage
SIEMENS	ET 200SP	6ES7132-6BH01-0BA0	14	SIMATIC ET 200SP, Digital output module, DQ 16x 24V DC/0,5A Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to BU-type A0, Colour Code CC00, substitute value output, module diagnostics for: short-circuit to L+ and ground, wire break, supply voltage
SIEMENS	ET 200SP	6ES7132-6HD01-0BB1	13	SIMATIC ET 200SP, Relay module, RQ NO 4x 120V DC..230VAC/5A ST. 4 normally open contacts, isolated contacts, packing unit: 1 piece, fits to BU-type B0 and B1, Colour Code CC40, substitute value output, module diagnostics for: supply voltage
SIEMENS	ET 200SP	6ES7134-6FF00-0AA1	2	SIMATIC ET 200SP, Analog input module, AI 8XU Basic, suitable for BU type A0, A1, Color code CC02, Module diagnostics, 16 bit
SIEMENS	ET 200SP	6ES7134-6HB00-0CA1	9	SIMATIC ET 200SP, Analog input module, AI 2x U/I 2-.4-wire High Feat., suitable for BU type A0, A1, Color code CC05, channel diagnostics, 16 bit, +/-0.1%
SIEMENS	ET 200SP	6ES7134-6GD01-0BA1	4	SIMATIC ET 200SP, ANALOG INPUT MODULE, AI 4XI 2-/4-WIRE STANDARD, PACKING UNIT: 1 PIECE, FITS TO BU-TYPE A0, A1, COLOR CODE CC03, MODULE DIAGNOSIS, 16BIT, +/-0,3%
SIEMENS	ET 200SP	6ES7134-6HB00-0DA1	8	SIMATIC ET 200SP, Analog input module, AI 2x U/I 2-.4-wire High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.3%
SIEMENS	ET 200SP	6ES7134-6HD01-0BA1	8	SIMATIC ET 200SP, ANALOG INPUT MODULE, AI 4XU/I 2-WIRE STANDARD, PACKING UNIT: 1 PIECE, FITS TO BU-TYPE A0, A1, COLOR CODE CC03, MODULE DIAGNOSIS, 16BIT, +/-0,3%
SIEMENS	ET 200SP	6ES7134-6JD00-0CA1	2	SIMATIC ET 200SP, Analog input module, AI 4xRTD/TC High Feature, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%, 2-/3-/4-wire
SIEMENS	ET 200SP	6ES7134-6PA01-0BU0	7	SIMATIC ET 200SP, analog input module, AI Energy Meter CT ST, for 1A or 5A current transformer, suitable for BU type U0, channel diagnostics
SIEMENS	ET 200SP	6ES7135-6GB00-0BA1	7	SIMATIC ET 200SP, Analog output module, AQ 2xI Standard, Pack quantity: 1 unit, suitable for BU type A0, A1, Color code CC00, Module diagnostics, 16 bit
SIEMENS	ET 200SP	6ES7135-6HB00-0DA1	6	SIMATIC ET 200SP, Analog output module, AQ 2x U/I High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.2%
SIEMENS	ET 200SP	6ES7136-6BA01-0CA0	18	SIMATIC DP, electronic module for ET 200SP, F-DI 8x 24 V DC HF, 15 mm width, up to PLe (ISO 13849-1)/ SIL3 (IEC 61508)
SIEMENS	ET 200SP	6ES7136-6DB00-0CA0	16	SIMATIC DP, Electronics module for ET 200SP, F-DQ 4X24 V DC/2A, 15 mm width, up to PL E (ISO 13849) up to SIL 3 (IEC 61508)
SIEMENS	ET 200SP	6ES7136-6PA00-0BC0	7	SIMATIC DP, POWER M. F-PM-E PPM PROFIsafe, for ET 200SP; 24 V DC safe shutdown of DQ and F-DQ up to PL D/SIL2 or PL E/SIL3 2 for safe dig. inputs 1 for safe dig. output PPM

SIEMENS	ET 200SP	6ES7138-6AA01-0BA0	2	SIMATIC ET 200SP, TM count 1x 24 V Counter module, 1 channel for 24 V incremental encoder or pulse encoder, 3 DI, 2 DQ Suitable for BU type A0, packing quantity: 1 unit,
SIEMENS	ET 200SP	6ES7155-6AR00-0AN0	12	SIMATIC ET 200SP, PROFINET interface module IM 155-6PN Basic, Max. 12 I/O modules, 2x integrated RJ45 sockets incl. server module
SIEMENS	ET 200SP	6ES7155-6AU01-0BN0	33	SIMATIC ET 200SP, PROFINET interface module IM 155-6PN Standard, max. 32 I/O modules, and 16 ET 200AL modules, single hot swap, incl. server module (6ES7193-6PA00-0AA0)
SIEMENS	ET 200SP	6ES7155-6AU01-0CN0	26	SIMATIC ET 200SP, PROFINET, 2-port interface module IM 155-6PN/2 High Feature, 1 slot for BusAdapter, max. 64 I/O modules and 16 ET 200AL modules, S2 redundancy, multi-hotswap, 0.25 ms, isochronous mode, optional PN strain relief, including server module
SIEMENS	ET 200SP	6ES7193-6AR00-0AA0	1	SIMATIC ET 200SP, BusAdapter BA 2xRJ45, 2 RJ45 sockets
SIEMENS	ET 200SP	6ES7193-6BP00-0BD0	1	SIMATIC ET 200SP, BaseUnit BU20-P12+A0+0B, BU type D0, push-in terminals, without AUX terminals, bridged to the left, WxH: 20 mm x 117 mm
SIEMENS	ET 200SP	6ES7193-6BP00-0BU0	37	SIMATIC ET 200SP, BaseUnit BU20-P16+A0+2B, BU-TYPE U0, Packaging Unit: 1 Pieces, Push-in terminals, w/o AUX-terminals, bridged to left BU, WxH: 20mm x 117mm
SIEMENS	ET 200SP	6ES7193-6BP20-0DA0	15	SIMATIC ET 200SP, BaseUnit BU15-P16+A10+2D, BU type A0, Push-in terminals, with 10 AUX terminals, New load group, WxH: 15 mmx141 mm
SIEMENS	ET 200SP	6ES7131-6BF01-0BA0	18	SIMATIC ET 200SP, Digital input module, DI 8x 24V DC Standard, type 3 (IEC 61131), sink input, (PNP, P-reading), Packing unit: 1 piece, fits to BU-type A0, Colour Code CC01, input delay time 0,05..20ms, module diagnostics for: short-circuit of sensor supply, wire break, supply voltage
SIEMENS	LOGO	6ED1055-1CB00-0BA0	2	LOGO! DM8 24 expansion module, PS/I/O: 24 V/24 V/trans., 4 DI/4 DO
SIEMENS	LOGO	6ED1055-1HB00-0BA0	2	LOGO! DM8 24R expansion module, PS/I/O: 24 V/24 V/relay, 2TE 4 DI/4 DO, AC/DC/NPN Input
SIEMENS	LOGO	6ED1055-1MD00-0BA1	4	LOGO! AM2 RTD expansion module, PS: 12/24 V DC, 2AI-50...+200 °C Pt100/1000
SIEMENS	LOGO	6ED1057-1BA00-0BA0	1	LOGO! TD cable, spare part for LOGO! TD length 2.5 m
SIEMENS	LOGO	6ED1058-0BA08-0YA1	2	LOGO! SOFT Comfort V8, single license for 1 installation E-SW, SW and documentation on DVD, 6 languages, executable on Windows XP, 7, 8, 10 (32- and 64-bit), Mac OSx 10.7 Lion to incl. Mac OSx El Capitan, Linux SUSE 11.3, SP3, K 3.0.76
SIEMENS	LOGO	6EP1332-1SH43	1	LOGO!Power 24 V/2.5 A Stabilized power supply input: 100-240 V AC (DC 110-300 V) output: DC 24 V/2, 5 A
SIEMENS	Power Supply	6EP1332-1SH71	2	SIMATIC S7-1200 Power Module PM1207 Stabilized power supply input: 120/230 V AC, output: DC 24 V/2,5 A
SIEMENS	Power Supply	6EP1436-2BA10	3	SITOP PSU300S 20 A stabilized power supply input: 400-500 V 3 AC output: 24 V DC/20 A
SIEMENS	Power Supply	6EP1437-2BA20	4	SITOP PSU300S 40 A stabilized power supply input: 400-500 V 3 AC output: 24 V DC/40 A
SIEMENS	Power Supply	6EP1336-1LB00	1	SITOP PSU100L 24 V/20 A Stabilized power supply input: 100-240 V AC output: 24 V DC/20 A
SIEMENS	Power Supply	6EP1333-2BA20	1	SITOP PSU100S 24 V/5 A Stabilized power supply input: 120/230 V AC, output: 24 V DC/5 A
SIEMENS	Power Supply	6EP1333-3BA10	4	SITOP PSU200M 5 A stabilized power supply input: 120/230-500 V AC output: 24 V DC/5 A *Ex approval no longer available*
SIEMENS	Power Supply	6EP1434-2BA10	3	SITOP PSU300S 10 A stabilized power supply input: 400-500 V 3 AC output: 24 V / 10 A DC

SIEMENS	Power Supply	6EP3436-8SB00-0AY0	11	SITOP PSU8200 24 V/20 A stabilized power supply input: 400-500 V 3 AC output: 24 V DC/20 A
SIEMENS	Power Supply	6EP3437-8SB00-0AY0	5	SITOP PSU8200 24 V/40 A stabilized power supply input: 400-500 V 3 AC output: 24 V DC/40 A
SIEMENS	Power Supply	6EP1334-2BA20	3	SITOP PSU100S 24 V/10 A Stabilized power supply input: 120/230 V AC, output: DC 24 V/10 A
SIEMENS	Profibus Connector	6ES7972-0BA42-0XA0	30	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s with inclined cable outlet, 15.8x 54x 39.5 mm (WxHxD), terminating resistor with isolating function, without PG socket
SIEMENS	Profibus Connector	6ES7972-0BA30-0XA0	4	SIMATIC DP, bus connection plug f. PROFIBUS w. inclined cable outlet, max. 1.5 Mbaud, insulation displacement method, 15x 57.6x 39.5 mm (WxHxD), without bus terminating resistor and programming device socket
SIEMENS	Profibus Connector	6ES7972-0BA52-0XA0	14	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, Insulation displacement method FastConnect, without PG socket 15.8x 59x 35.6 mm (BxHxD)
SIEMENS	Profibus Connector	6ES7972-0BB12-0XA0	30	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 64x 35.6 mm (WxHxD), terminating resistor with isolating function, With PG receptacle
SIEMENS	Profibus Connector	6ES7972-0BB42-0XA0	30	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s with inclined cable outlet, 15.8x 54x 39.5 mm (WxHxD), terminating resistor with isolating function, With PG receptacle
SIEMENS	Profibus Connector	6ES7972-0BB52-0XA0	30	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, Insulation displacement method FastConnect, With PG receptacle 15.8x 59x 35.6 mm (BxHxD)
SIEMENS	Profibus Connector	6ES7972-0CB35-0XA0	1	SIMATIC S7, TS Adapter II for SIMATIC Teleservice RS-232 and integrated analog modem; connection to MPI/DP power supply MPI or external 24 V; parameter assignment via USB
SIEMENS	Profibus Connector	6ES7972-0AA02-0XA0	8	SIMATIC DP, RS485 repeater For connection of PROFIBUS/MPI bus systems with max. 31 nodes max. baud rate 12 Mbit/s, Degree of protection IP20 Improved user handling
SIEMENS	Memory Card	6ES7954-8LC03-0AA0	11	SIMATIC S7, memory card for S7-1x 00 CPU/SINAMICS, 3, 3 V Flash, 4 MB
SIEMENS	Memory Card	6ES7954-8LF03-0AA0	14	SIMATIC S7, MEMORY CARD FOR S7-1X00 CPU/SINAMICS, 3,3 V FLASH, 24 MBYTE
SIEMENS	Memory Card	6ES7954-8LL03-0AA0	8	SIMATIC S7, MEMORY CARD FOR S7-1X00 CPU, 3,3 V FLASH, 256 MBYTE
SIEMENS	Memory Card	6ES7954-8LE04-0AA0	7	SIMATIC S7, memory cards for S7-1x00 CPU/SINAMICS, 3, 3V Flash, 12 MB
SIEMENS	Cable	6ES7901-0BF00-0AA0	1	SIMATIC S7, MPI cable for connection of SIMATIC S7 and PG via MPI 5 m
SIEMENS	Cable	6XV1830-0EH10	2000	PROFIBUS FC Standard Cable GP, bus cable 2-wire, shielded, special configuration for quick assembly,
SIEMENS	Battery Cell	6ES7971-0BA00	38	SIMATIC S7-400, Backup battery 3.6 V/2.3 AH for PS 405 4 A/10 A/20 A and PS 407 4 A/10 A/20 A
SIEMENS	Battery Cell	6ES7971-1AA00-0AA0	14	SIMATIC S7, Backup battery (LI) 3.6 V/min. 0.85 Ah, for for S7-300 CPUs and S5-90U
SIEMENS	SCALANCE	6GK5004-1BF00-1AB2	1	SCALANCE XB004-1LD unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 4x 10/100 Mbit/s twisted pair ports with RJ45 sockets; 1 x 100 Mbit/s single-mode glass fiber-optic cable port with SC socket; manual available as a download .

SIEMENS	SCALANCE	6GK5208-0BA00-2AB2	1	SCALANCE XB208 managed Layer 2 IE switch 8x 10/100 Mbit/s RJ45 ports 1x console port; diagnostics LED redundant power supply IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.
SIEMENS	HMI	6AV2123-2GB03-0AX0	2	SIMATIC HMI, KTP700 Basic, Basic Panel, Key/touch operation, 7" TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD
SIEMENS	HMI	6AV2123-2MA03-0AX0	1	SIMATIC HMI, KTP1200 Basic DP, Basic Panel, Key/touch operation, 12" TFT display, 65536 colors, PROFIBUS interface, configurable as of WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD
SIEMENS	HMI	6AV2124-0QC02-0AX1	2	SIMATIC HMI TP1500 Comfort, Comfort Panel, touch operation, 15" widescreen TFT display, 16 million colors, PROFINET interface, MPI/PROFIBUS DP interface, 24 MB configuration memory, WEC 2013, configurable as of WinCC Comfort V14 SP1 with HSP, ambient temperature up to 50 °C (up to 55 °C with restrictions)
SIEMENS	Power Module	6SL3130-1TE31-0AA0	1	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 167 A, 100KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE
3-May-2025			Thanks for Watching	